



AVA-DC-SRG-ISL

AVA-DC-SRG-ISL SURGE PROTECTOR AND ISOLATOR

OVERVIEW

- Single Channel DC Power for range of DC 10 ~ 36V
- DC 12/0.65A (Max.) protection up to 8W
- DC Power protector and isolator
- ESD Protection, efficiency up to 80%
- DC Female in & DC Male out connection
- Compatible with HD-TVI, CVI, AHD, and Analog cameras
- Passive type, no power required
- Plug-and-play solution

SPECIFICATIONS

PROPERTIES	
Transmission Signal	1 Channel
Transmission Distance	HD-TVI / HD-CVI / AHD Up to 250m (820ft)
Category Type	UTP CAT5 / 5E / 6
VIDEO TRANSMISSION	
Coaxial Video Connector	BNC-M
Twisted-Pair Video Connector	Push-Terminal
Compatible Format	HD-TVI / HD-CVI / AHD / ANALOG (MAGIC)
Resolution	Up to 5MP HD for All Video Formats
Anti-Interference	>60db
PROTECTION	
TVS	Built in TVS for Surge Protection
Coaxial Cable Connector	2KV(common-code) Per : IEC1000-4-5
UTP Cable Connector	2KV(different-code) 4KV(common-code) Per: IEC1000-4-5