





AVC-TD51F28

NDAA


5MP HD-TVI INDOOR FIXED DOME CAMERA


OVERVIEW

- 5MP HD-TVI (default), CVI, AHD, ANALOG (960H)
- Maximum Resolution: 2592 x 1944
- 2.8mm Fixed Lens
- Smart IR Illumination Up to 66ft (20m).
- True Day/Night
- Digital WDR
- Digital NR
- AGC
- BLC
- DIP Switch
- DC12V
- 30 FPS
- NDAA Compliant

DIMENSIONS

Unit: inch(mm)





OPTIONAL ACCESSORIES



AVM-CWM-EDV-L1
COMPACT WALL MOUNT





SPECIFICATIONS

| CAMERA | |
|------------------------------|---|
| Image Sensor | 1/2.7" Progressive Scan CMOS |
| Resolution | 5MP |
| Image Size | 2592 x 1944 |
| Video Output | 1-channel BNC Video Output |
| Image System | PAL / NTSC |
| Electronic Shutter | 1/15s to 1/50,000s |
| IR Distance | Up to 66ft. |
| Video Formats | HD-TVI / AHD / CVI / CVBS (Analog) |
| Frame Rate | 5AHD/5TVI: 5MP @20fps (NTSC / PAL), AHD/CVI/TVI: 4MP @30fps (NTSC) / @25fps (PAL), 2MP @30fps (NTSC) / @25fps (PAL) |
| Min. Illumination | 0.05luxF1.2(AGC ON), 0Lux with IR ON |
| Lens | Fixed 2.8mm Lens |
| Lens Mount | M12 |
| S/N Ratio | 39dB |
| Function Control | OSD, Control over Coax (UTC) |
| IMAGE | |
| Day & Night | EXT / Auto / Color / BW (Black and White) |
| Digital WDR | |
| | Yes (2D DNR) |
| | Yes |
| Auto White Balance (AWB) | Yes |
| Backlight Compensation (BLC) | Yes |
| Edge Brightness Compensation | Yes |
| Defog | |
| HLC | |
| | Yes |
| Mirror Image | |
| | Yes |
| Image Setting | Yes |
| | Auto / Manual |
| GENERAL | |
| Angle Adjustment | |
| | DC 12V (±10%) |
| Power Consumption | |
| | -22°~122° F (-30°~50° C) |
| Dimensions | Ø4.72" x 3.62" (Ø120mm x 92mm) |