

AVK-N1100

AVYCON NETWORK KEYBOARD

OVERVIEW

CONTENTS

- Support remote configuration by WEB client
- Seamless integration with AVYCON and ONVIF PTZ's
- Support multi-language operation
- Support PTZ mode and platform mode, up to 256 speed domes controllable in PTZ mode
- Support the playback control of TV wall client
- Support macro setup and calling
- Support linked display window, PIP, roaming control





SPECIFICATIONS

DESCRIPTION	
Model	AVK-N1100
Control Mode	PTZ Mode and Platform Mode
	AVYCON PTZ Cameras
	AVYCON Plug & Play Cameras Specialty PTZ Cameras
LCD Screen	58X44(2.8") Blue Screen
	Four-Dimensional Rocker
NETWORK	
	IPV4, HTTP, TCP, MSSP
	1*RJ45 100M/1000M Adaptive Ethernet Port
	Two Standard Serial Ports: RS485 × 1, RS232 × 1
GENERAL	
	Temperature: -10°C~60°C/Humidity: 10%~90%
	PoE (802.3af) / DC 12V 2A
Power Consumption	
	6.17lbs(2.8kg)
	16.5"(W)x 10.2"(D)x 6.7"(H)(420mmx260mmx170mm)
Warranty	3 Years

All the contents on the AVYCON's digital and printed marketing materials include product names, part number, unique identification letters, etc., are trademarks of AVYCON. Any unauthorized use or distribution of trademarked contents is strictly prohibited by law. In addition, graphical designs, images, features, and specifications on such materials may differ from the actual products and subject to change without notice. For the latest product information/specification please visit our website or contact one of our product specialists at marketing@avycon.com